


Sidewalls, cleats and tracking guides

The following samples of PVC belts are indicative of our range . Further types are available.




All PVC belts (and some PU belts) can be equipped with longitudinal or transverse profiles.

We supply T-cleats, V-profiles and sidewalls in various sizes and types.

Standard material: PU or PVC

Temperature range: -10 to +80 °C


Square profiles white and green



All sizes in mm

designatio n	10 x 10	15 x 10	15 x 15	20 x 15
A	10	10	15	15
B	10	15	15	20


V-Profile PVC white and green; V-Profile PU white, plain or notched (for small turn rounds)



All sizes in mm

designatio n	6 x 4	8 x 5	10 x 6	13 x 8	17 x 11	22 x 14	30 x 16
A	4	5	6	8	11	14	16
B	4	5	6	7	11	14	16
C	6	8	10	13	17	22	30

T-cleats 90°




	height in mm			
PVC white or green	20	40	50	60
PU white	25	40	60	-

T-cleats 60°



	height in mm		
PVC white or green	40	50	60
PU white	70	-	-

Standard and minimal sidewalls



Recommended roller-diameter: min. 150mm. In special cases you can get them smaller after consultation.

Available heights in mm: 20 – 30 – 40 – 50 – 60 – 70 – 80 - 100

